

ROLLING FLOOR

Interactive



GOB Technology

Interactive

Flat Surface

Strong Load

Custom Size

IP65

Multiple Pixel Pitches Available

P1.9、P2.6、P3.9mm
Versatile for Various Scenarios,
Supports U3D Adaptive Format



IP65 Protection

Enhanced durability with GOB technology

Interactive Data
30ms response speed,
zero blind spots

Infrared Sensors
16 sensors per module

High Load Capacity Supports up to 100kg per point

Seamless Precision

Innovative design with no gaps or visible screws

Specifications

Model	P1.95	P2.6	P3.91
LED	SMD1010	SMD1415	SMD2020
Module Size (mm)	250*125	500*125	500*125
Module Resolution	128x 64	192 x 48	128 x 32
System	Self-Developed System		
Brightness (CD/m ²)	>600cd	>800cd	>800cd
Weight (KG/m ²)	16KGS	16KGS	16KGS
Scanning Method	1/32	1/24	1/16
Max Power Consumption	512w/m ²		
Average Power Consumption	170w/m ²		
Refresh Rate	3840HZ		
Waterproof Rating	IP65 (Front) / IP41 (Rear)		

Interactive Floor Screen

Redefining smart interaction with 16 sensors per module. Supports multi-user operation, ensuring stability and smooth performance for large-scale scenarios.